

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

* * * * *

CUTTING TABLE FENCE

* * * * *

INVENTORS

JOHN P. KENNELLY
JACK A. LINN

ATTORNEY'S DOCKET NO. KE27-001

862020 DEB60760

CUTTING TABLE FENCE

TECHNICAL FIELD

The present invention relates to cutting guides in general and more particularly to a removable fence for a cutting table.

BACKGROUND OF THE INVENTION

Numerous fence designs have been produced for the cutting tables of various cutting tools such as woodworking table saws. The fence on a table saw is used, in general, to hold an edge of a workpiece at a specific angle, usually parallel to a cutting blade 13. The fence must be held parallel to the blade to minimize the kerf width, and to avoid dangerous "kick-back." A precisely parallel fence also is a significant factor in cutting accuracy.

Much of recent development in design of fences for cutting tables has focused on accuracy, or the ability for the fence to maintain an accurate state of parallelism with the saw blade. However, a high degree of accuracy has not been maintained, at least not without involving complex and difficult to install mechanisms. Such mechanisms most often result in a practically permanent installation of the fence on the saw, since removal and remounting of the fence is most often a laborious, time consuming chore.

An example of a high quality, accurate retrofit fence for table saws is described in U.S. Patent 4, 521, 006 to Waters. This fence makes use of pulley mounted cables that extend in an endless loop

1 along opposite sides and across one end of the saw table. Two flights
2 of the cable run parallel to each of the front and back edges of the
3 table. Two of the four flights move in the same direction as the cable
4 is moved about the pulleys. Blocks are secured to these parts of the
5 cable. The blocks are releasably mounted to locking devices provided
6 at opposite ends of the fence cutting guide. Two clamping levers are
7 used to secure the fence to "L" shaped brackets that are bolted to the
8 table. In order to remove the fence from the table, the blocks must
9 be moved laterally toward the table, away from engagement with the
10 locking levers. This requires the user to reach under the fence, shift
11 one block from engagement with the associated locking lever, then walk
12 around the saw and perform the same steps to remove the remaining
13 block from the lever on that side of the table. Now the fence may
14 be removed, but only by sliding it off an end of the table.
15 Remounting the fence involves the above operation in reverse.

16 U.S. Patent 2, 805,479 to Droste discloses a work table for sheet
17 materials in which opposite ends of a fence-like bar is mounted to
18 cables that extend about pairs of pulleys. The pulleys are rotatably
19 mounted at ends of the table. Two of the pulleys are interconnected
20 by a drive shaft for rotation in unison. Thus rotation of the shaft will
21 cause corresponding substantially equal motion of the cables about the
22 pulleys. The fence spans the table, with ends clamped to the cables
23 by screw and nut combinations. The fence may be removed by
24 loosening the clamps.

The above examples of cable and pulley mounted fences operate well to hold a fence in accurate position on across a table surface, but both are relatively complex. Also neither of the above apparatus are easily removable from the cutting table when use requires removal of the fence.

It is therefor an object of the present invention to provide a cutting table fence that is simple in construction, easy to mount to an existing cutting table, and which includes a cutting guide that is easily removable from the table.

The above and still further objects and advantages will become apparent from the following description which, taken with the accompanying drawings, disclose a preferred form of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the invention are described below with reference to the following accompanying drawings.

Fig. 1 is a perspective view of an operator and table saw with a preferred form of the present fence in operation thereon;

Fig. 2 is a top plan view of the preferred fence on a table saw;

Fig. 3 is an end elevation view of the preferred fence on a table saw;

Fig. 4 is a side elevation view as viewed from the left in Fig. 3;

Fig. 5 is an enlarged fragmented sectional view taken substantially along line 5-5 in Fig. 3;

1 Fig. 6 is a view similar to Fig. 5 only showing the cutting guide
2 lifted clear of remaining mechanism and table saw;

3 Fig. 7 is an enlarged fragmented sectional view taken substantially
4 along line 7-7 in Fig. 3;

5 Fig. 8 is an enlarged fragmented detail plan view of a lug
6 adjuster and associated components of the preferred fence; and

7 Fig. 9 is a fragmented detail view showing an aligning lug
8 received between chain rollers.

9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

This disclosure of the invention is submitted in furtherance of the constitutional purposes of the U.S. Patent Laws "to promote the progress of science and useful arts" (Article 1, Section 8).

In general reference to Fig. 1 of the drawings, a cutting table is shown as identified by the reference numeral 10. The particular cutting table 10 exemplified is a table saw of the type commonly used in the woodworking industry. Other types of cutting tables may also be used with the present fence, which is generally shown at 12.

The exemplary table 10 includes a table top with a substantially planar top surface 14 and substantially parallel forward and rearward side edges 16, 18. The size and configuration of the table top may vary according to the nature of the cutting device, but typically is rectangular and the edges 16, 18 are usually substantially parallel. The edges 16, 18 are joined by side edges 20, 22 that are also substantially parallel and perpendicular to the forward and rearward edges 16, 18 (Fig. 2).

Preferred forms of the present fence 12 are adapted to be mounted to existing cutting table tops, and may be produced as a retrofit for a variety of table forms and sizes. However, it is also possible for the present fence to be produced in combination with a cutting table.

In general terms, the preferred fence 12 includes an elongated cutting guide 24, and motion conditioning members 26 configured for

2
a
a
1 attachment to the cutting table 10. The motion conditioning
2 members 26 are releasably connected by forward (Fig. ⁸5) and rearward
3 (Fig. ⁵8) aligning lugs 28, 29 to the cutting guide 24 to permit
4 substantially linear motion of the elongated cutting guide 24 while
5 holding the cutting guide at a prescribed angular relation. The aligning
6 lugs 28, 29 are configured to permit the elongated cutting guide 24 to
7 be lifted upwardly from engagement with the motion conditioning
8 members 26.

9 In preferred forms, the motion conditioning members 26 are
10 configured for attachment to forward and rearward guide rails 32, 33
11 that are mountable by bracket assemblies 30 (Figs. 1, 2) to the cutting
12 table 10. The bracket assemblies 30 mount the guide rails 32, 33 to
13 the table in such a manner that the guide rails 32, 33 are substantially
14 parallel to one another and to the respective forward and rearward
15 cutting table edges 16, 18.

16 The brackets 30 are preferably "L" shaped and may be provided
17 with mounting slots and spacers that will enable secure mounting by
18 means of standard bolt or bolt and nut combinations to various cutting
19 tables. In the example illustrated, the brackets 30 are secured to the
20 table side edges 20, 22. It is also possible that other bracket
21 configurations and other mounting positions could be used to secure the
22 guide rails 32, 33 in position in relation to the cutting table 10.

23 In a preferred form, the guide rails 32, 33 are comprised of
24 elongated channel members, preferably formed of a rigid material such

as steel or aluminum. The guide rails preferably extend at least the full length of the forward and rearward table edges 16, 18. The rails 32, 33 include respective forward and rearward elongated top guide surface 34, 36 that are positioned by the bracket assemblies 30 in parallel relation to and slightly below the top surface 14 of the cutting table 10.

A preferred example of the motion conditioning members 26 is shown as endless chains 37, 38 on respective guide rails 32, 33. The chains are trained about pairs of sprockets ^{40' and 41, 41'} 40, ~~42~~ that are rotatably mounted at ends of the respective guide rails 32, 33. The chains 37, 38 include ^{39, 39'} a working flights that extend along and are slidably supported on the guide rail surfaces 34, 36 (Fig. 9).

Chains 37, 38 are advantageously identical conventional roller-type ^{chains} ~~chain~~ with sprocket tooth receiving spaces between successive rollers. Such spaces are equally spaced apart in order to mate in driving connection with the teeth of the sprocket. The spaces are also used by the aligning lugs 28, 29 to releasably position the cutting guide 24 as will be understood from further description below.

A shaft 44 (Figs. 1, 2, 4 and 7) interconnects a stub shaft 42 that mounts one of the sprockets on one guide rail with another stub shaft 43 that mounts another one of the sprockets on the remaining guide rail. Sleeves 45 interconnect the stub shafts 42, 43 axially with the shaft 44. Set screws 46 (Figs. 2, 7) operably lock the stub shafts 42, 43 to the shaft 44 so rotation of the shaft assembly will

1 result in rotation of all the sprockets in unison, and corresponding
2 identical movement of the chains 37, 38.

3 In preferred forms, the shaft assembly is extendible and adjustable
4 to accommodate tables of different widths. To this end, the sleeves 45
5 are adjustably affixed to the shaft sections by set screws 46 to allow
6 axial adjustment of the shaft assembly and rotational alignment of the
7 sprockets. A cutting guide adjustment knob 48 is secured to the
8 rearward end of one stub shaft 43, enabling a user to rotate the shaft
9 and thereby move the chains and attached cutting guide 24 across the
10 cutting table 10.

11 Chain tension may be selectively adjusted by chain tensioners 47
12 (Figs. 2 and 3) which mount the two sprockets ^{40, 41} at ends of the guide
13 rails that are opposite to the shaft attached sprockets. The
14 tensioners 47 are preferably of a yoke and screw variety mounted within
15 the guide rails, though other tensioner configurations could also be used.

16 The illustrated cutting guide 24 is preferably formed of an
17 extruded aluminum channel, but could be any other appropriate material
18 or construction suitable for use as a straight cutting guide. The guide
19 is preferably longer than the width of the table (between forward and
20 rearward edges 16, 18), and is mounted to forward and rearward base
21 blocks 50, 51.

22 In preferred forms, the forward and rearward base blocks 50, 51
23 are mounted at opposed ends of the cutting guide 24. The blocks may
24 be formed of billet machined aluminum, cast, or otherwise formed and

862040 DEB60T60

1 attached adjacent opposite ends of the cutting guide by bolts or other
2 appropriate fastening technology.

3 Base blocks 50, 51 preferably include chain receiving grooves 52,
4 53 respectively that fit over working flights of the chains 37, 38. The
5 grooves 52, 53 are substantially parallel and oriented normal to the
6 cutting guide to be received over the working flights of the chains.
7 Bottom surfaces of the base blocks may slidably rest against top
8 surfaces of the guide rails.

9 The aligning lugs 28, 29 are preferably secured to the respective
10 base blocks 50, 51 within the chain receiving grooves 52, 53 and extend
11 downwardly to be releasably received in the spaces between chain rollers
12 (see Figs. 5 and 9). In preferred forms, both aligning lugs 28, 29 are
13 shaped as cylindrical pins, preferably of steel with pointed ends to
14 facilitate insertion of the aligning lugs between chain rollers. The
15 diameters of the aligning lugs are substantially equal to the spacing
16 between adjacent chain rollers. Thus when the aligning lugs 28, 29
17 lowered into the spaces along the chains, the associated base blocks and
18 cutting guide are releasably secured to the chain for movement across
19 the cutting table. Further, the cutting guide, base blocks and aligning
20 lugs can be easily lifted upwardly from engagement with the chains.

21 One of the aligning lugs, preferably the forward lug 28 is may be
22 mounted by a lug adjustor 54 (Figs. 2, 8) that is operatively connected
23 between the cutting guide and the one lug. The lug adjustor 54 is
24 configured to adjustably position the one lug laterally with respect to

1 the cutting guide 24. Such lateral adjustment results in angular
2 positioning of the cutting guide 24 when the lug is positioned in
3 engagement with the associated chain 37.

4 In the illustrated example, and with specific reference to Fig. 8,
5 the lug adjustor 54 is mounted to the forward base block 50. The
6 exemplary adjustor 54 is comprised of a slide 55 movably mounted
7 within a complimentary way ^{55'} formed in the base block 50. An anchor
8 screw 56 is received through a slot 57 in the slide 55 and threadably
9 engages the base block 50. The anchor screw 56 may be loosened to
10 allow the slide 55 to move translationally within the way ^{55'} through a
11 distance limited by the length of the slot 57.

12 The forward aligning lug 28 is rigidly attached to the slide 55 and
13 projects downwardly into the chain receiving groove 52 of the base
14 block 50. Any sliding movement of the slide 55 will thus result in
15 corresponding movement of the aligning lug 28.

16 Fine angular alignment of the cutting guide is accomplished by
17 turning a headed adjustment screw 60. The adjustment screw 60
18 extends through a portion of the base block 50 which is sandwiched
19 between the screw head and an appropriate spring clip 58. The
20 adjustment screw 60 is thus held by the screw head and spring clip 58
21 against axial movement. Threads on the adjustment screw 60 engage
22 mating threads within the slide 55. Rotation of the adjustment screw
23 will thus result in sliding movement of the slide 55 and the attached
24

forward aligning lug 28. Such motion results in corresponding angular adjustment of the cutting guide 24.

A remaining one of the aligning lugs, preferably rearward aligning lug 29 is rigidly secured to one of the base blocks, preferably the rearward base block 51 (Fig. 9). Aligning lug 29 is fixed in position on the associated base block 51 and extends downwardly within the chain receiving groove where it may be releasably received within the adjacent spaces along the chain 38. Thus the aligning lug 29 is stationary relative to the cutting guide, and will act as a pivot point about which the cutting guide may be angularly adjusted in response to turning of the adjusting screw 60.

In preferred forms of the present fence 12, a locking mechanism 65 is provided in operable connection to the cutting guide 24. The locking mechanism 65 in general is configured to secure the cutting guide in a selected position along the table 10.

The preferred locking mechanism exemplified herein includes a clamp bar 66 (Figs. 5, 6) mounted to one of the base blocks (preferably the rearward base block 51) by a tightener 67 that is configured to clamp the remaining base block (preferably the forward base block 50) to an adjacent side edge of the table 10.

More specifically, the clamp bar 66 is mounted at an end of a jack screw 70. The jack screw end is journalled in the clamp bar 66 and the clamp bar slides in a guideway 68 formed in the base block 51 in such a manner that rotation of the jack screw 70 will not result in

0910930 070298 252040 DEB0T60

1 corresponding rotational motion of the clamp bar. However, the threads
2 of the jack screw engage mating threads formed in the rearward base
3 block 51, so that rotation of the jack screw 70 will result in forward
4 or rearward motion of the clamp bar.

5 A knob 71 is provided to enable manual rotation of the jack
6 screw. The knob 71 may thus be turned to move the clamp bar 66
7 against the rearward guide rail 33. This action pulls the forward base
8 block 50 (Fig. 4) against the forward edge 16 of the table 10, thereby
9 securely clamping the cutting guide in position relative to the table.

10 The above clamping action will cause the chains, especially the
11 forward chain 37 to shift slightly toward the forward edge 16 of the
12 table. This shifting motion is accommodated by allowing a limited
13 amount of axial "play" of the sprockets within the guide rails 32, 33 so
14 the chains need not bend during the clamping action.

15 It is pointed out that the locking mechanism described above may
16 take other forms. For example, known forms of cam type locking
17 mechanisms (not shown) may be provided in place of the jack screw
18 and knob arrangement described above.

19 Given the above technical description, installation and operation
20 of the presently preferred fence 12 may be readily understood.

21 The present fence 12 may be supplied in four basic components:
22 the cutting guide 24 (with the base blocks 50, 51 and associated
23 elements mounted thereon); the forward guide rail 32 (with brackets 30,
24 forward chain 37 and sprockets 40⁴⁰ mounted thereon); the rearward

1 guide rail 33 (with the remaining brackets 30, rearward chain 38 and
2 sprockets 41⁴¹ mounted thereon); and the shaft 44 (with the sleeves 45
3 mounted thereon).

4 Given the above components, the fence 12 may be mounted to
5 a table 10 by simply bolting the brackets 30 to the appropriate table
6 sides. Many conventional table saws include mounting holes in the
7 table sides that can be used in this procedure. If such holes are not
8 provided, an ordinary drill may be used to form mounting holes.

9 Appropriate slots³¹ (Fig. 1) in the mounting brackets 30 will allow
10 elevational positioning of the guide rails 32, 33. This may be done
11 with the cutting guide 24 resting on the table top surface 14 and with
12 the base blocks 50, 51 overhanging the front and rearward table
13 edges 16, 18. The rails 32, 33 are adjusted elevationally (with the
14 brackets 30 loosely mounted) until the bottom surfaces of the base
15 blocks 50, 51 just touch the respective top guide surfaces 34, 36 and
16 the aligning lugs 28, 29 are received within adjacent spaces between
17 rollers of the chains 37, 38. When proper elevational adjustment is
18 achieved, the bolts securing the brackets 30 to the table are tightened.

19 Now the shaft 44 may be mounted. This is done by sliding the
20 sleeves 45 inwardly from the shaft ends to allow positioning of the shaft
21 in axial alignment with the stub shafts 42, 43. The sleeves 45 are then
22 slid outwardly to overlap and receive ends of the respective stub shafts.
23 All but one of the set screws 46 are then tightened. The one
24

2025 RELEASE UNDER E.O. 14176

1 remaining set screw 46 is left loose to facilitate alignment of the cutting
2 guide.

3 Cutting guide alignment may be achieved by first lowering the
4 cutting guide onto the table. As this is done, the aligning lugs 28, 29
5 will slip downwardly into position within spaces between rollers of the
6 chains 37, 38. Now the cutting guide 24 is pushed across the table
7 until it touches and shifts into flush abutment with the cutting blade 13.
8 The cutting guide 24 is now parallel with the cutting blade 13 and the
9 final set screw 46 may be tightened, thereby locking all the sprockets
10 and chains in precise relation. Rotation of the cutting guide adjusting
11 knob 48 will now result in corresponding rotation of all sprockets, and
12 uniform, in unison movement of the chains 37, 38. The chains 37, 38
13 move the cutting guide 24 across the table 10, all the while maintaining
14 the cutting guide 24 in the set, precise parallel relation to the cutting
15 blade 13.

16 If further precision positioning of the cutting guide is desired, the
17 adjustment screw 60 may be used to shift the forward end of the
18 cutting guide 24 to the desired angular position. Such fine adjustment
19 is best accomplished using appropriate fine measuring tools such as a
20 conventional dial indicator for further precision adjustment of the cutting
21 guide. The present fence 12 is now ready for use.

22 In describing use, it will be assumed that a 3 inch cut is to be
23 made on a workpiece 80 as shown in Fig. 1. To set the fence, the
24 user simply turns the adjusting knob 48 driving the chains to move the

cutting guide to a point 3 inches away from the cutting blade 13. Any appropriate measuring device may be used to assure proper positioning. Alternatively, a scale (not shown) of conventional nature may be mounted to the rearward guide rail 33 for this purpose.

Once the proper cutting guide position is selected, the locking jack screw knob 71 may be tightened to lock the cutting guide in position. As the knob 71 is turned, the clamp bar 66 will move against the rearward guide rail 33 and pull the forward base block 50 firmly against the forward edge 16 of the cutting table, thus locking the cutting guide in position, with the chains holding the guide in the set alignment. The cut may now be made.

If use of the cutting table is desired without the fence 12, the cutting guide 24 may simply be lifted from the table. The aligning lugs 28, 29 will slip upwardly from engagement with the chains 37, 38 as the cutting guide is lifted. Now the table 10 is free and unobstructed.

When it is again desired to re-mount the cutting guide to the table, the user simply lowers the guide onto the table. The aligning lugs 28, 29 will slide into whatever chain spaces are immediately below, and the precise previously set angular adjustment is again established. This relationship will be maintained regardless of where the cutting guide is positioned on the table, and use can begin immediately as described above.

2025 RELEASE UNDER E.O. 14176

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

In compliance with the statute, the invention has been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the invention is not limited to the specific features shown and described, since the means herein disclosed comprise preferred forms of putting the invention into effect. The invention is, therefore, claimed in any of its forms or modifications within the proper scope of the appended claims appropriately interpreted in accordance with the doctrine of equivalents.